

5 Таблица подбора мотор-редукторов РС - КРС

Р1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.09	373.3	2.0	6.5	7.5	PC 30	56A2	2800	27
	280.0	2.6	5.0	10				
	186.7	3.7	3.5	15				
	140.0	4.8	2.5	20				
	112.0	5.7	2.8	25				
	93.3	6.5	2.3	30				
	70.0	8.1	1.7	40				
	56.0	10	1.4	50				
	46.7	11	1.1	60				
	35.0	13	0.9	80				
	186.7	3.9	4.6	7.5	PC 30	56B4	1400	27
	140.0	5.0	3.6	10				
	93.3	7.1	2.5	15				
	70.0	9.0	2.0	20				
	56.0	10	2.0	25				
	46.7	12	1.7	30				
	35.0	14	1.2	40				
	28.0	17	1.0	50				
	23.3	19	0.9	60				
	120.0	5.9	3.4	7.5	PC 30	63A6	900	27
	90.0	7.6	2.6	10				
	60.0	11	1.9	15				
	45.0	13	1.5	20				
	36.0	15	1.5	25				
	30.0	17	1.2	30				
	22.5	21	1.0	40				
	18.0	24	0.7	50				
	28.0	19	2.0	50	PC 40	56B4	1400	28
	23.3	21	1.7	60				
	17.5	26	1.3	80				
	14.0	29	1.0	100				
	30.0	19	2.6	30	PC 40	63A6	900	28
	22.5	24	1.9	40				
	18.0	27	1.5	50				
	15.0	31	1.3	60				
	11.3	37	1.0	80				
	9.0	41	0.8	100				
	4.7	88	0.8	300	KPC 30 - PC 40	56B4	1400	36
	15.0	32	2.3	60	PC50	63A6	900	29
	11.3	37	1.8	80				
	9.0	42	1.3	100				
	3.5	107	1.2	400	KPC 30 - PC 50	56B4	1400	36
	2.8	123	1.0	500				
	2.3	159	0.9	600				
	1.9	185	0.8	750				
	1.6	212	0.7	900				
	0.9	360	1.1	1500	KPC 40 - PC 75	56B4	1400	36
	0.78	404	1.0	1800				
	0.58	496	0.7	2400				
	0.5	609	0.9	3000	KPC 40 - PC 90	56B4	1400	37
	0.35	548	0.8	4000				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.12	186.7	5.2	3.4	7.5	PC30	63A4	1400	27
	140.0	6.7	2.7	10				
	93.3	9.5	1.9	15				
	70.0	12	1.5	20				
	56.0	14	1.5	25				
	46.7	16	1.3	30				
	35.0	19	0.9	40				
	28.0	23	0.8	50				
	120.0	7.9	2.5	7.5	PC30	63B6	900	27
	90.0	10	2.0	10				
	60.0	14	1.4	15				
	45.0	18	1.1	20				
	36.0	20	1.1	25	PC 30	63B6	900	27
	30.0	23	0.9	30				
	46.7	17	2.6	30	PC 40	63A4	1400	28
	35.0	21	1.9	40				
	28.0	25	1.5	50				
	23.3	28	1.3	60				
	17.5	34	1.0	80				
	14.0	38	0.8	100				
	30.0	25	1.9	30	PC 40	63B6	900	28
	22.5	32	1.4	40				
	18.0	36	1.2	50				
	15.0	41	0.9	60				
	23.3	29	2.3	60	PC 50	63A4	1400	29
	17.5	35	1.9	80				
	14.0	40	1.4	100				
	22.5	32	2.6	40	PC 50	63B6	900	29
	18.0	38	2.0	50				
	15.0	42	1.7	60				
	11.3	50	1.4	80				
	9.0	56	1.0	100				
0.18	4.7	119	1.2	300	KPC 30 - PC 50	63A4	1400	36
	3.5	142	0.9	400				
	2.8	164	0.7	500				
	1.6	325	1.2	900	KPC 40 - PC 75	63A4	1400	36
	1.2	399	0.9	1200				
	0.8	547	0.9	1800	KPC 40 - PC 90	63A4	1400	37
	0.58	695	0.9	2400				
	0.5	884	1.2	3000	KPC 50 - PC 110	63A4	1400	37
	0.35	784	1.0	4000				
	0.28	928	0.80	5000				
	373.3	4.0	3.2	7.5	PC 30	63A2	2800	27
	280.0	5.2	2.5	10				
	186.7	7.5	1.7	15				
	140.0	10	1.3	20				
	112.0	11	1.4	25				
	93.3	13	1.1	30				
	70.0	16	0.9	40				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.18	186.7	7.8	2.3	7.5	PC 30	63B4	1400	27
	140.0	10	1.8	10				
	93.3	14	1.3	15				
	70.0	18	1.0	20				
	56.0	21	1.0	25	PC 30	63B4	1400	27
	46.7	24	0.8	30				
	93.3	14	2.4	30	PC 40	63A2	2800	28
	70.0	18	1.8	40				
	56.0	21	1.4	50				
	70.0	19	2.0	20	PC 40	63B4	1400	28
	56.0	23	1.7	25				
	46.7	26	1.7	30				
	35.0	32	1.3	40				
	28.0	38	1.0	50				
	23.3	43	0.8	60				
	45.0	29	1.5	20	PC 40	71A6	900	28
	36.0	34	1.3	25				
	30.0	38	1.3	30				
	22.5	47	1.0	40				
	46.7	24	2.1	60	PC 50	63A2	2800	29
	35.0	30	1.5	80				
	28.0	34	1.2	100				
0.25	35.0	33	2.3	40	PC 50	63B4	1400	29
	28.0	39	1.9	50				
	23.3	43	1.6	60				
	17.5	52	1.2	80				
	14.0	60	0.9	100				
	18.0	56	1.4	50	PC 50	71A6	900	29
	15.0	63	1.1	60				
	11.3	75	0.9	80				
	15.0	66	2.1	60	PC 63	71A6	900	30
	11.3	79	1.6	80				
	9.0	90	1.4	100				
	2.3	362	1.1	600	KPC 40 - PC 75	63B4	1400	36
	1.9	435	0.9	750				
	1.6	487	0.8	900				
	1.2	629	1.0	1200	KPC 40 - PC 90	63B4	1400	37
	0.93	735	0.8	1500				
	373.3	5.6	2.3	7.5	PC 30	63B2	2800	27
	280.0	7.2	1.8	10				
	186.7	10	1.3	15				
	140.0	13	0.9	20				
	112.0	16	1.0	25				
	93.3	18	0.8	30				

5 Таблицы подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.25	186.7	11	3.6	7.5	PC 40	71A4	1400	28
	140.0	14	2.8	10				
	93.3	21	1.9	15				
	70.0	27	1.5	20				
	56.0	32	1.2	25				
	46.7	36	1.3	30				
	35.0	44	0.9	40				
	120.0	17	2.6	7.5	PC 40	71B6	900	28
	90.0	22	2.0	10				
	60.0	31	1.4	15				
	45.0	40	1.1	20				
	36.0	48	0.9	25				
	30.0	53	0.9	30				
	35.0	42	1.1	80	PC 50	63B2	2800	29
	28.0	48	0.8	100				
	70.0	27	2.7	20	PC 50	71A4	1400	29
	56.0	32	2.2	25				
	46.7	37	2.3	30				
	35.0	46	1.7	40				
	28.0	54	1.4	50				
	23.3	60	1.1	60				
	17.5	72	0.9	80				
	45.0	40	1.9	20	PC 50	71B6	900	29
	36.0	48	1.5	25				
	30.0	54	1.7	30				
	22.5	67	1.2	40				
	18.0	78	1.0	50				
	15.0	88	0.8	60				
	28.0	56	2.4	50	PC 63	71A4	1400	30
	23.3	63	2.0	60				
	17.5	78	1.6	80				
	14.0	87	1.4	100				
	18.0	81	1.8	50	PC 63	71B6	900	30
	15.0	92	1.5	60				
	11.3	110	1.2	80				
	9.0	125	1.0	100				
	17.5	82	2.3	80	PC 75	71A4	1400	31
	14.0	94	1.9	100				
	11.3	117	1.7	80	PC 75	71B6	900	31
	9.0	133	1.4	100				
	3.5	336	1.1	400	КРС 40- PC 75	71A4	1400	36
	2.8	384	0.8	500				
	2.3	512	1.2	600	КРС 40- PC 90	71A4	1400	37
	1.9	598	0.9	750				
	1.6	667	0.8	900				
	1.2	943	1.3	1200	КРС 50 - PC 110	71A4	1400	37
	0.93	1064	1.2	1500				
	0.78	1195	1.1	1800				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.37	373.3	8.2	1.6	7.5	PC 30	63C2	2800	27
	280.0	11	1.2	10				
	186.7	15	0.8	15				
	373.3	8.4	3.3	7.5	PC 40	71A2	2800	28
	280.0	11	2.6	10				
	186.7	16	1.9	15				
	140.0	21	1.4	20				
	112.0	25	1.1	25				
	186.7	16	2.4	7.5	PC 40	71B4	1400	28
	140.0	21	1.9	10				
	93.3	31	1.3	15				
	70.0	39	1.0	20				
	56.0	47	0.8	25				
	46.7	53	0.8	30				
	112.0	25	2.0	25	PC 50	71A2	2800	29
	93.3	29	2.2	30				
	70.0	37	1.6	40				
	56.0	44	1.2	50				
	46.7	50	1.0	60				
	35.0	62	0.7	80				
	140.0	22	3.3	10	PC 50	71B4	1400	29
	93.3	31	2.4	15				
	70.0	40	1.8	20				
	56.0	48	1.5	25				
	46.7	55	1.5	30				
	35.0	68	1.1	40				
	28.0	80	0.9	50	PC 50	71B4	1400	29
	23.3	89	0.8	60				
	120.0	25	3.3	7.5	PC 50	80A6	900	29
	90.0	33	2.5	10				
	60.0	47	1.8	15				
	45.0	60	1.3	20				
	36.0	72	1.0	25				
	30.0	80	1.1	30				
	35.0	71	2.1	40	PC 63	71B4	1400	30
	28.0	83	1.6	50				
	23.3	94	1.4	60				
	17.5	115	1.1	80				
	14.0	129	0.9	100				
	45.0	60	2.4	20	PC 63	80A6	900	30
	36.0	74	1.9	25				
	30.0	82	2.1	30				
	22.5	102	1.6	40				
	18.0	120	1.2	50				
	15.0	137	1.0	60				
	23.3	98	2.0	60	PC 75	71B4		31
	17.5	121	1.6	80				
	14.0	139	1.3	100				
	18.0	126	1.8	50	PC 75	80A6		31
	15.0	144	1.5	60				
	11.3	173	1.2	80				
	9.0	196	1.0	100				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.37	4.7	405	1.0	300	КРС 40 - РС 75	71B4	1400	36
	3.5	498	0.7	400				
	11.3	185	1.7	80	РС 90	80A6	900	32
	9.0	212	1.3	100				
	4.7	402	1.5	300	КРС 40 - РС 90	71B4	1400	37
	3.5	523	1.2	400				
	2.8	611	0.9	500				
	2.3	757	0.8	600				
	1.9	950	1.3	750	КРС 50 - РС 110	71B4	1400	37
	1.6	1079	1.2	900				
	1.2	1396	0.8	1200				
0.55	373.3	13	2.2	7.5	РС 40	71B2	2800	28
	280.0	17	1.8	10				
	186.7	24	1.3	15				
	140.0	31	0.9	20				
	112.0	37	0.8	25				
	186.7	24	1.6	7.5	РС 40	71C4	1400	28
	140.0	32	1.3	10				
	93.3	46	0.9	15				
	140.0	31	1.7	20	РС 50	71B2	2800	29
	112.0	38	1.4	25				
	93.3	43	1.5	30				
	70.0	55	1.1	40				
	56.0	65	0.8	50				
	46.7	74	0.7	60				
	186.7	25	2.9	7.5	РС 50	80A4	1400	29
	140.0	32	2.2	10	РС 50	80A4	1400	29
	93.3	46	1.6	15				
	70.0	59	1.2	20				
	56.0	71	1.0	25				
	46.7	81	1.0	30				
	120.0	38	2.2	7.5	РС 50	80B6	900	29
	90.0	49	1.7	10				
	60.0	69	1.2	15				
	45.0	89	0.9	20				
	70.0	56	1.9	40	РС 63	71B2	2800	30
	56.0	67	1.5	50				
	46.7	77	1.2	60				
	35.0	95	0.9	80				
	28.0	109	0.7	100				
	70.0	61	2.2	20	РС 63	80A4	1400	30
	56.0	73	1.8	25				
	46.7	83	1.9	30				
	35.0	105	1.4	40				
	28.0	124	1.1	50				
	23.3	140	0.9	60				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.55	60.0	71	2.2	15	PC 63	80B6	900	30
	45.0	90	1.6	20				
	36.0	109	1.3	25				
	30.0	123	1.4	30				
	22.5	152	1.1	40				
	35.0	99	1.3	80	PC 75	71B2	2800	31
	28.0	114	1.0	100				
	35.0	108	2.0	40	PC 75	80A4	1400	31
	28.0	129	1.6	50				
	23.3	146	1.4	60				
	17.5	180	1.1	80				
	14.0	206	0.9	100				
	30.0	128	2.0	30	PC 75	80B6	900	31
	22.5	159	1.5	40				
	18.0	187	1.2	50				
	15.0	214	1.0	60				
	17.5	189	1.5	80	PC 90	80A4	1400	32
	14.0	221	1.2	100				
	18.0	198	2.0	50	PC 90	80B6	900	32
	15.0	224	1.6	60				
	11.3	275	1.1	80				
	9.0	315	0.9	100				
	9.3	306	2.0	300	КРС 40- PC 90	71B2	2800	37
	7.0	403	1.5	400				
	5.6	470	1.2	500				
	17.5	201	2.6	80	PC 110	80A4	1400	33
	14.0	236	2.0	100				
	11.3	294	1.9	80	PC 110	80B6	900	33
	9.0	338	1.5	100				
	4.7	639	2.0	300	КРС 50 - PC 110	80A4	1400	37
	3.5	826	1.4	400				
	2.8	984	1.1	500				
	2.3	1181	1.0	600				
	1.9	1411	0.9	750				
0.75	373.3	17	1.6	7.5	PC 40	71C2	2800	28
	280.0	23	1.3	10				
	186.7	32	1.0	15				
	373.3	17	3.0	7.5	PC 50	80A2	2800	29
	280.0	23	2.4	10				
	186.7	33	1.7	15				
	140.0	42	1.3	20				
	112.0	51	1.0	25				
	93.3	58	1.1	30				
	186.7	34	2.1	7.5	PC 50	80B4	1400	29
	140.0	44	1.6	10				
	93.3	63	1.2	15				
	70.0	81	0.9	20				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.75	140.0	43	2.3	20	PC 63	80A2	2800	30
	112.0	52	1.8	25				
	93.3	60	2.0	30				
	70.0	77	1.4	40				
	56.0	91	1.1	50				
	46.7	104	0.9	60				
	93.3	64	2.2	15	PC 63	80B4	1400	30
	70.0	83	1.6	20				
	56.0	100	1.3	25				
	46.7	114	1.4	30				
	35.0	143	1.0	40				
	120.0	52	2.9	7.5	PC 63	90S6	900	30
	90.0	68	2.3	10				
	60.0	97	1.6	15				
	45.0	123	1.2	20				
	36.0	149	0.9	25				
	30.0	167	1.0	30				
	46.7	109	1.3	60	PC 75	80A2	2800	31
	28.0	156	0.8	100				
	56.0	102	2.0	25	PC 75	80B4	1400	31
	46.7	117	2.0	30				
	35.0	147	1.5	40				
	28.0	177	1.2	50				
	23.3	200	1.0	60				
	60.0	98	2.4	15	PC 75	90S6	900	31
	45.0	126	1.9	20				
	36.0	153	1.4	25				
	30.0	174	1.5	30				
	22.5	216	1.1	40				
	35.0	141	1.6	80	PC 90	80A2	2800	32
	28.0	166	1.2	100				
	28.0	184	1.8	50	PC 90	80B4	1400	32
	23.3	212	1.5	60				
	17.5	258	1.1	80				
	14.0	302	0.9	100				
	30.0	179	2.6	30	PC 90	90S6	900	32
	22.5	226	1.8	40				
	18.0	271	1.4	50				
	15.0	306	1.1	60				
	7.0	549	1.1	400	КРС 40 - PC 90	71C2	2800	37
	5.6	642	0.9	500				
	17.5	274	1.9	80	PC 110	80B4	1400	33
	14.0	322	1.5	100				
	15.0	325	2.1	60	PC 110	90S6	900	33
	11.3	401	1.4	80				
	9.0	462	1.1	100				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
0.75	9.3	446	2.8	300	КРС 50 - РС 110	80A2	2800	37
	7.0	563	2.1	400				
	5.6	687	1.6	500				
	4.7	871	1.5	300	КРС 50 - РС 110	80B4	1400	37
	3.5	1126	1.1	400				
	11.3	407	2.1	80	РС 130	90S6	900	34
	9.0	470	1.7	100				
1.1	373.3	25	2.1	7.5	РС 50	80B2	2800	29
	280.0	33	1.6	10				
	186.7	48	1.2	15				
	140.0	62	0.9	20				
	186.7	48	2.1	15	РС 63	80B2	2800	30
	140.0	63	1.6	20				
	112.0	77	1.2	25				
	93.3	88	1.4	30				
	70.0	113	1.0	40				
	120.0	76	2.0	7.5	РС 63	90L6	900	30
	90.0	99	1.5	10				
	60.0	142	1.1	15				
	45.0	180	0.8	20				
	186.7	50	2.6	7.5	РС 63	90S4	1400	30
	140.0	65	2.0	10				
	93.3	93	1.5	15				
	70.0	122	1.1	20				
	56.0	146	0.9	25				
	46.7	167	1.0	30				
	112.0	78	1.9	25	РС 75	80B2	2800	31
	93.3	90	1.9	30				
	70.0	116	1.4	40				
	56.0	139	1.1	50				
	46.7	160	0.9	60				
	90.0	100	2.3	10	РС 75	90L6	900	31
	60.0	144	1.6	15				
	45.0	184	1.3	20				
	36.0	225	1.0	25				
	30.0	256	1.0	30				
	93.3	96	2.1	15	РС 75	90S4	1400	31
	70.0	123	1.7	20				
	56.0	150	1.3	25				
	46.7	171	1.3	30				
	35.0	216	1.0	40				
	35.0	207	1.1	80	РС 90	80B2	2800	32
	28.0	244	0.8	100				
	36.0	231	1.6	25	РС 90	90L6	900	32
	30.0	263	1.8	30				
	22.5	331	1.2	40				
	18.0	397	1.0	50				
	15.0	448	0.8	60				

5 Таблица подбора мотор-редукторов РС - КРС

Р1 (кВт)	п2 (об/мин)	М2 (Нм)	сервис- фактор	i	Габарит редуктора		п1 (об/мин)	стр.
1.1	35.0	225	1.6	40	РС 90	90S4	1400	32
	28.0	270	1.3	50				
	23.3	311	1.0	60				
	22.5	345	2.3	40	РС 110	90L6	900	33
	18.0	414	1.8	50				
	15.0	476	1.4	60				
	11.3	588	1.0	80				
	28.0	281	2.3	50	РС 110	90S4	1400	33
	23.3	324	1.9	60				
	17.5	402	1.3	80				
	14.0	473	1.0	100				
	9.3	654	1.9	300	КРС 50 - РС 110	80B2	2800	37
	7.0	845	1.4	400				
	5.6	1007	1.1	500				
	11.3	598	1.4	80	РС 130	90L6	900	34
	9.0	689	1.1	100				
	17.5	408	2.1	80	РС 130	90S4	1400	34
	14.0	480	1.5	100				
1.5	373.3	35	1.5	7.5	РС 50	80C2	2800	28
	280.0	45	1.2	10				
	186.7	65	0.9	15				
	186.7	68	1.9	7.5	РС 63	90L4	1400	29
	140.0	89	1.5	10				
	93.3	127	1.1	15				
	70.0	166	0.8	20				
	373.3	35	2.7	7.5	РС 63	90S2	2800	29
	280.0	46	2.1	10				
	186.7	66	1.6	15				
	140.0	86	1.2	20				
	112.0	105	0.9	25				
	93.3	120	1.0	30				
	120.0	105	2.0	7.5	РС 75	100LA6	900	30
	90.0	137	1.7	10				
	60.0	196	1.2	15				
	56.0	189	0.8	50	РС 75	90S2	2800	30
	46.7	218	0.7	60				
	140.0	90	2.2	10	РС 75	90L4	1400	30
	93.3	130	1.5	15				
	70.0	168	1.3	20				
	56.0	205	1.0	25				
	46.7	233	1.0	30				
	280.0	46	3.1	10	РС 75	90S2	2800	30
	186.7	67	2.2	15				

5 Таблица подбора мотор-редукторов РС - КРС

Р1 (кВт)	п2 (об/мин)	М2 (Нм)	сервис- фактор	i	Габарит редуктора		п1 (об/мин)	стр.
1.5	140.0	87	1.8	20	PC 75	90S2	2800	31
	112.0	106	1.4	25				
	93.3	123	1.4	30				
	70.0	158	1.0	40				
	90.0	138	2.7	10	PC 90	100LA6	900	32
	60.0	201	2.1	15				
	45.0	258	1.5	20				
	36.0	314	1.2	25				
	30.0	358	1.3	30				
	70.0	172	2.1	20	PC 90	90L4	1400	32
	56.0	210	1.6	25				
	46.7	239	1.7	30				
	35.0	307	1.2	40				
	28.0	368	0.9	50				
	23.3	424	0.8	60				
	56.0	194	1.4	50	PC 90	90S2	2800	32
	46.7	227	1.1	60				
	45.0	264	2.7	20	PC 110	100LA6	900	33
	36.0	322	2.4	25				
	30.0	363	2.3	30				
	22.5	471	1.7	40				
	18.0	565	1.3	50				
	15.0	649	1.1	60				
	35.0	319	2.2	40	PC 110	90L4	1400	33
	28.0	384	1.7	50				
	23.3	442	1.4	60				
	17.5	548	0.9	80				
	46.7	236	2.0	60	PC 110	90S2	2800	33
	35.0	299	1.3	80				
	28.0	353	1.0	100				
2.2	9.3	891	1.4	300	KPC 50 - PC 110	90S2	2800	37
	7.0	1153	1.0	400				
	5.6	1373	0.8	500				
	22.5	478	2.3	40	PC 130	100LA6	900	34
	18.0	573	1.8	50				
	15.0	659	1.4	60				
	11.3	815	1.1	80				
	17.5	557	1.5	80	PC 130	90L4	1400	34
	14.0	655	1.1	100				
	373.3	51	1.8	7.5	PC 63	90L2	2800	30
	280.0	67	1.5	10				
	186.7	97	1.1	15				
	186.7	100	1.8	7.5	PC 75	100LA4	1400	31
	140.0	132	1.5	10				
	93.3	191	1.0	15				
	373.3	51	2.5	7.5	PC 75	90L2	2800	31
	280.0	68	2.1	10				
	186.7	98	1.5	15				
	140.0	128	1.3	20				
	112.0	156	1.0	25				
	93.3	180	0.9	30				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	Стр.
2.2	186.7	101	2.9	7.5	PC 90	100LA4	1400	32
	140.0	134	2.3	10				
	93.3	194	1.9	15				
	70.0	252	1.4	20				
	56.0	308	1.1	25				
	46.7	351	1.2	30				
	120.0	156	2.2	7.5	PC 90	112M6	900	32
	90.0	203	1.8	10				
	60.0	294	1.4	15				
	45.0	378	1.0	20				
	140.0	131	2.0	20	PC 90	90L2	2800	32
	112.0	159	1.6	25				
	93.3	185	1.7	30				
	70.0	237	1.2	40				
	56.0	285	0.9	50				
	70.0	255	2.5	20	PC 110	100LA4	1400	33
	56.0	315	2.2	25				
	46.7	356	2.0	30				
	35.0	468	1.5	40				
	28.0	563	1.2	50				
	23.3	648	1.0	60				
	90.0	205	3.5	10	PC 110	112M6	900	33
	60.0	298	2.6	15				
	45.0	388	1.9	20				
	36.0	473	1.6	25				
	30.0	532	1.6	30				
	112.0	163	3.1	25	PC 110	90L2	2800	33
	93.3	187	3.0	30				
	70.0	246	2.1	40				
	56.0	296	1.7	50				
	46.7	347	1.4	60				
	35.0	468	2.2	40	PC 130	100LA4	1400	34
	28.0	563	1.7	50				
	23.3	648	1.4	60				
	17.5	816	1.0	80				
	36.0	479	2.2	25	PC 130	112M6	900	34
	30.0	546	2.1	30				
	22.5	700	1.6	40				
	18.0	840	1.2	50				
	15.0	966	1.0	60				
	35.0	438	1.3	80	PC 130	90L2	2800	34
	28.0	525	1.0	100				
2.2	28.0	570	2.5	50	PC 150	100LA4	1400	35
	23.3	657	1.9	60				
	17.5	816	1.4	80				
	14.0	960	1.0	100				

5 Таблица подбора мотор-редукторов РС - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
3	373.3	70	1.9	7.5	PC 75	100LA2	2800	31
	280.0	92	1.6	10				
	186.7	137	1.4	7.5	PC 75	100LB4	1400	31
	140.0	180	1.1	10				
	93.3	261	0.8	15				
	373.3	71	3.0	7.5	PC 90	100LA2	2800	32
	280.0	92	2.6	10				
	186.7	138	2.1	7.5	PC 90	100LB4	1400	32
	140.0	182	1.7	10				
	93.3	264	1.4	15				
	70.0	344	1.0	20				
	56.0	420	0.8	25				
	46.7	479	0.9	30				
	93.3	264	2.5	15	PC 110	100LB4	1400	33
	70.0	348	1.9	20				
	56.0	430	1.6	25				
	46.7	485	1.5	30				
	35.0	638	1.1	40				
	28.0	767	0.9	50				
	120.0	212	3.1	7.5	PC 110	132S6	900	33
	90.0	280	2.5	10				
	60.0	406	1.9	15				
	45.0	528	1.4	20				
	56.0	430	2.2	25	PC 130	100LB4	1400	34
	46.7	491	2.1	30				
	35.0	638	1.6	40				
	28.0	767	1.3	50				
	23.3	884	1.0	60				
	17.5	1113	0.8	80				
	90.0	280	3.4	10	PC 130	132S6	900	34
	60.0	406	2.6	15				
	45.0	535	1.9	20				
	36.0	653	1.6	25	PC 130	132S6	900	34
	30.0	745	1.6	30				
	22.5	955	1.2	40				
	28.0	778	1.8	50	PC 150	100LB4	1400	35
	23.3	896	1.4	60				
	17.5	1113	1.0	80				
	14.0	1310	0.8	100				
4	373.3	93	1.4	7.5	PC 75	112M2	2800	31
	280.0	123	1.2	10				
	186.7	182	1.0	7.5	PC 75	112M4	1400	31
	140.0	240	0.8	10				
	373.3	94	2.2	7.5	PC 90	112M2	2800	32
	280.0	123	1.9	10				
	186.7	184	1.6	7.5	PC 90	112M4	1400	32
	140.0	243	1.3	10				
	93.3	352	1.0	15				
	70.0	458	0.8	20				

5 Таблица подбора мотор-редукторов PC - КРС

P1 (кВт)	n2 (об/мин)	M2 (Нм)	сервис- фактор	i	Габарит редуктора		n1 (об/мин)	стр.
4	140.0	243	2.5	10	PC 110	112M4	1400	33
	93.3	352	1.9	15				
	70.0	464	1.4	20				
	56.0	573	1.2	25				
	46.7	647	1.1	30				
	120.0	283	2.3	7.5	PC 110	132M6	900	33
	90.0	374	1.9	10				
	60.0	541	1.4	15				
	56.0	573	1.6	25	PC 130	112M4	1400	34
	46.7	655	1.6	30				
	35.0	851	1.2	40				
	28.0	1023	1.0	50				
	23.3	1179	0.8	60				
	120.0	287	3.1	7.5	PC 130	132M6	900	34
	90.0	374	2.6	10				
	60.0	541	2.0	15				
	45.0	713	1.5	20				
	36.0	870	1.2	25				
	28.0	1037	1.4	50	PC 150	112M4	1400	35
	23.3	1195	1.1	60				
	17.5	1484	0.8	80				
5.5	186.7	253	2.2	7.5	PC 110	132S4	1400	33
	140.0	334	1.8	10				
	93.3	484	1.4	15				
	70.0	638	1.0	20				
	140.0	334	2.5	10	PC 130	132S4	1400	34
	93.3	490	1.9	15				
	70.0	645	1.4	20				
	56.0	788	1.2	25				
	46.7	900	1.2	30				
	35.0	1171	0.9	40				
	70.0	645	2.0	20	PC 150	132S4	1400	35
	56.0	788	1.5	25				
	46.7	934	1.3	30				
	35.0	1171	1.3	40				
	28.0	1426	1.0	50				
	23.3	1643	0.8	60				
7.5	186.7	345	1.6	7.5	PC 110	132L4	1400	33
	140.0	455	1.3	10				
	93.3	660	1.0	15				
	186.7	349	2.1	7.5	PC 130	132L4	1400	34
	140.0	455	1.8	10				
	93.3	668	1.4	15				
	70.0	880	1.0	20				
	56.0	1074	0.9	25				
	46.7	1228	0.8	30				
	35.0	1596	0.7	40				
	70.0	880	1.5	20	PC 150	132L4	1400	35
	56.0	1074	1.1	25				
	46.7	1274	0.9	30				
	35.0	1596	1.0	40				

Р1 (кВт)	п2 (об/мин)	М2 (Нм)	сервис- фактор	i	Габарит редуктора		п1 (об/мин)	стр.
9.2	186.7	424	1.3	7.5	PC 110	132M4	1400	33
	186.7	428	1.8	7.5	PC 130	132M4	1400	34
	140.0	559	1.5	10				
	93.3	819	1.1	15				
	70.0	1079	0.8	20				
	56.0	1318	0.7	25				
	70.0	1079	1.2	20	PC 150	132M4	1400	35
	56.0	1318	0.9	25				
	46.7	1563	0.8	30				
	35.0	1958	0.8	40				
11	186.7	512	2.3	7.5	PC 150	160M4	1400	35
	140.0	675	1.8	10				
	93.3	990	1.3	15				
	70.0	1291	1.0	20				
	56.0	1576	0.8	25				
15	186.7	698	1.7	7.5	PC 150	160L4	1400	35
	140.0	921	1.3	10				
	93.3	1351	0.9	15				
	70.0	1760	0.7	20				

Для заметок



ООО "ЭДС"
(495) 979-59-00
(901) 519-59-00
eds@eds-privod.ru
